



6V 7.0Ah

REPLACEMENT BATTERY

Model: BLA 6V 7.0A

Specifications

Cells Per Unit	3
Normal Voltage	6V
Capacity	7.5Ah @ 20 hour rate to 1.75V per cell @ 77°F
Weight	Approx. (1.13 ± 3%) kg (2.45 lbs)
Maximum Discharge Current	75A (5 sec)
Internal Resistance	Approximately 18mΩ full charged @ 77°F
Operating Temperature Range	Discharge: -4°F ~ 140°F Charge: 32°F ~ 122°F Storage: -4°F ~ 140°F
Nominal Operating Temperature Range	77°F ± 5°F
Float Charging Voltage	6.75 ~ 6.90 VDC/unit average @ 77°F
Maximum Charging Current	2.25A
Equalization and Cycle Service	7.20V ~ 7.50 VDC/unit average @ 77°F
Self Discharge	Valve regulated lead acid (VRLA) batteries can be stored for more than 6 months at 77°F. Self-discharge ratio less than 3% per month at 77°F. Please charge batteries before using.
Terminal	F1 (0.187) / F1 (0.187) includes (1) F2 terminal adapter
Container Material	ABS (UL94-HB)
Battery Dimensions	6.0"W x 3.8"H x 1.4"D



- Rechargeable
- 90-Minute Minimum Emergency Run Time
- Multiple Use, Including Security Systems, Electronics Power Back-Up, Medical Equipment and More!
- Sealed Lead-Calcium
- Non-Spillable
- 1 Year Warranty
- UL Certified



MH62885



**Precision Consumer
Products Group, LLC.**

11024 Balboa Boulevard • Suite 1710
Granada Hills, CA 91344

1-866-237-9983
www.precisioncpg.com